



IEC:1010-1
IEC:1010-2-032

NEW



SPECIFICATIONS

Specifications	Range	Best Accuracy
Model		UT223A
Leakage Current and Current (A)	Range	0.0mA~499A
		500A~999A
		1000A~2999A
		3000A~4000A
	Resolution	0.1A
Test Range	AC 0.A~4000A	✓
Features		
Display Mode	Four Digits LCD Display	✓
Clamp Size	108mm×148mm (can clamp electric cable of 108mm diameter, or 160mm×4mm flat cable and steel earth wires)	✓
Auto Range		✓
RS-232 Interface		✓
Data Storage	99 Groups	✓
LCD Backlight		✓
Date Hold		✓
Overload Protection	OL	✓
Auto Power Off	5 Minutes	✓
Low Battery Indication	≤5.2V	✓
Test Model	Clamp CT, integral mode	✓



■ UT223A

GENERAL CHARACTERISTICS

Power Supply	6V DC(LR6×4 alkaline dry batteries)
LCD Size	47mm×28.5mm
Product Color	Red + Grey
Product Weight	1.5Kg(Included Batteries)
Product Size	350mm×180mm×55mm
Standard Accessories	Batteries, RS232 Interface Cable, Software CD, Toolbox
Standard Individual Packing	Gif Box, English Manual, Warranty Card, Toolbox
Standard Quantity Per Carton	6 Pcs
Standard Carton Measurement	610mm × 375mm × 320mm
Standard Carton Gross Weight	35Kg